



Fuels Perspective on Stochastic Pre-Ignition

2020 CRC Stochastic Pre-Ignition Workshop
September 29, 2020

Allen A. Aradi, PhD
Shell Projects and Technology Development – Future Mobility Gasoline

Cautionary note


The companies in which Royal Dutch Shell plc directly and indirectly owns investments are separate legal entities. In this presentation “Shell”, “Shell Group” and “Royal Dutch Shell” are sometimes used for convenience where references are made to Royal Dutch Shell plc and its subsidiaries in general. Likewise, the words “we”, “us” and “our” are also used to refer to Royal Dutch Shell plc and its subsidiaries in general or to those who work for them. These terms are also used where no useful purpose is served by identifying the particular entity or entities. “Subsidiaries”, “Shell subsidiaries” and “Shell companies” as used in this presentation refer to entities over which Royal Dutch Shell plc either directly or indirectly has control. Entities and unincorporated arrangements over which Shell has joint control are generally referred to as “joint ventures” and “joint operations”, respectively. Entities over which Shell has significant influence but neither control nor joint control are referred to as “associates”. The term “Shell interest” is used for convenience to indicate the direct and/or indirect ownership interest held by Shell in an entity or unincorporated joint arrangement, after exclusion of all third-party interest.

This presentation contains forward-looking statements (within the meaning of the U.S. Private Securities Litigation Reform Act of 1995) concerning the financial condition, results of operations and businesses of Royal Dutch Shell. All statements other than statements of historical fact are, or may be deemed to be, forward-looking statements. Forward-looking statements are statements of future expectations that are based on management’s current expectations and assumptions and involve known and unknown risks and uncertainties that could cause actual results, performance or events to differ materially from those expressed or implied in these statements. Forward-looking statements include, among other things, statements concerning the potential exposure of Royal Dutch Shell to market risks and statements expressing management’s expectations, beliefs, estimates, forecasts, projections and assumptions. These forward-looking statements are identified by their use of terms and phrases such as “aim”, “ambition”, “anticipate”, “believe”, “could”, “estimate”, “expect”, “goals”, “intend”, “may”, “objectives”, “outlook”, “plan”, “probably”, “project”, “risks”, “schedule”, “seek”, “should”, “target”, “will” and similar terms and phrases. There are a number of factors that could affect the future operations of Royal Dutch Shell and could cause those results to differ materially from those expressed in the forward-looking statements included in this presentation, including (without limitation): (a) price fluctuations in crude oil and natural gas; (b) changes in demand for Shell’s products; (c) currency fluctuations; (d) drilling and production results; (e) reserves estimates; (f) loss of market share and industry competition; (g) environmental and physical risks; (h) risks associated with the identification of suitable potential acquisition properties and targets, and successful negotiation and completion of such transactions; (i) the risk of doing business in developing countries and countries subject to international sanctions; (j) legislative, fiscal and regulatory developments including regulatory measures addressing climate change; (k) economic and financial market conditions in various countries and regions; (l) political risks, including the risks of expropriation and renegotiation of the terms of contracts with governmental entities, delays or advancements in the approval of projects and delays in the reimbursement for shared costs; and (m) changes in trading conditions. No assurance is provided that future dividend payments will match or exceed previous dividend payments. All forward-looking statements contained in this presentation are expressly qualified in their entirety by the cautionary statements contained or referred to in this section. Readers should not place undue reliance on forward-looking statements. Additional risk factors that may affect future results are contained in Royal Dutch Shell’s Form 20-F for the year ended December 31, 2018 (available at www.shell.com/investor and www.sec.gov). These risk factors also expressly qualify all forward-looking statements contained in this presentation and should be considered by the reader. Each forward-looking statement speaks only as of the date of this presentation, October 8th 2019. Neither Royal Dutch Shell plc nor any of its subsidiaries undertake any obligation to publicly update or revise any forward-looking statement as a result of new information, future events or other information. In light of these risks, results could differ materially from those stated, implied or inferred from the forward-looking statements contained in this presentation.

We may have used certain terms, such as resources, in this presentation that the United States Securities and Exchange Commission (SEC) strictly prohibits us from including in our filings with the SEC. U.S. investors are urged to consider closely the disclosure in our Form 20-F, File No 1-32575, available on the SEC website www.sec.gov.

Outline

- Fuels Perspective on Stochastic Preignition
 - Why is stochastic pre-ignition (SPI) a problem?
 - Challenge to optimizing SI-ICEs on efficiency and emissions
 - Root causes
 - Lubricant
 - Fuel
 - Fuel – PM/PN
 - PM Index (PMI)
 - Injector deposits
 - Suggested solution
 - Low PMI (<1.80), high octane (RON 96+) fuel
 - Additives




01

SPI LINK TO PM/PM

PM/PN Upward drift directly correlates to LSPI/SPI events

Aromatics heavy ends (C9/9+) have a chemical and physical effect on SPI

LSPI/PMPN Fuel	A	B	C
T90, °C	123.2	149.5	185.2
FBP, °C	170.2	194	208.7
Density, kg/m3	730.9	758.4	759.1
RON	97.6	97.7	97.6
MON	87.1	87.1	87.1
EtOH, vol%	10.7	10.2	10.2
Aro, vol%	9.6	30.8	30.9
Aro, C8 vol%	8	24.1	6.1
Aro, C9 vol%	0.3	1.2	4.4
Aro, C10+	0.8	5	19.9
Aro, C11+	2.3		1.5
Isoparaffins	51.9	41.8	39.4
Paraffins	73.3	53.3	53
Naphthenes	20.3	5.8	5.5
Olefins	4.9	5	4.8
ASVP, kPa	61.1	50.4	73.1
DVPE, kPa	55.2	44.9	66.8
PMI	0.49	1.36	2.83




- Test fuels demonstrated extreme differences in LSPI count at 1500 rpm/21 bar BMEP with the baseline oil
- Fuel A yielded zero events, while Fuel C resulted in an extremely high LSPI count
- Fuel LSPI count can increase or decrease with Oil formulation
- Fuel C unlikely to be found in marketplace


- 1) Kar, A. et al. "Assessing the impact of lubricant and fuel composition on LSPI and emissions in a turbocharged gasoline direct injection engine." SAE 2020-01-0610.
- 2) Tanaka, D. et al. "Effects of Fuel Properties Associated with In-Cylinder Behavior on Particulate Number from a Direct Injection Gasoline Engine." SAE 2017-01-1002.
- 3) Wiese, W. et al. "Effects of Fuel Composition, Additives and Injection Parameters on Particulate Formation of Gasoline DI Engines." 39th International Vienna Motor Symposium (26-27 April 2018)

Relationship between PMPN and LSPI


RESULTS - 21 BAR BMEP BASE OIL, FUEL A - TEST 1 - TR636




RESULTS - 21 BAR BMEP BASE OIL, FUEL B - TEST 1 - TR643




RESULTS - 21 BAR BMEP BASE OIL, FUEL C - TEST 1 - TR626



PN/PM INVESTIGATION - FUEL B - LSPI TEST RESULTS-TIME ALIGNED




PN/PM INVESTIGATION - FUEL C - LSPI TEST RESULTS-TIME ALIGNED



- LSPI frequency increase with increasing PM/PN
- Each LSPI event associated with a PM peak spike
- Time alignment shows the LSPI event to lead the PM peak spike



SAE 2020-01-0610

Start of Ignition vs Fuels Impact on PMPN: (wall wetting)





Base fuel impact during stationary start of injection (SOI) sweeps

- Heavy aromatics (C9+) and heavy paraffin fuels due to low volatility lead to high PN emissions due to combustion chamber wall films at early SOIs.



Wiese, W. et al. "Effects of Fuel Composition, Additives and Injection Parameters on Particulate Formation of Gasoline DI Engines." 39th International Vienna Motor Symposium (26-27 April 2018)

Test Cycles vs Fuels Impact on PMPN: (vehicle testing)



For selected base fuels the PN emissions were measured for the WLTC/RDE test cycles

- ❑ Heavy aromatics (C9+) on the endurance runs on the bench engine contribute to PN-drift for the highway part of the test cycles.
- ❑ Heavy aromatics (C9+) and heavy paraffin fuels due to low fuel volatility lead to higher cold start PN emissions, which correlates to SOI sweep results on the bench engine. Fuels behave similar in both drive cycles, but RDE limit is more challenging.

Wiese, W. et al. "Effects of Fuel Composition, Additives and Injection Parameters on Particulate Formation of Gasoline DI Engines." 39th International Vienna Motor Symposium (26-27 April 2018)

02

SOLUTIONS


2) Injector cleaning additives

Conifer, C. et al. "Injector Fouling and its Impact on Engine Emissions and Spray Characteristics in Gasoline Direct Injection Engines." SAE Technical Paper Series 2017-01-0808

1) Low PM/PN fuel (PMI <1.80)

Wiese, W. et al. "Effects of Fuel Composition, Additives and Injection Parameters on Particulate Formation of Gasoline DI Engines." 39th International Vienna Motor Symposium (26-27 April 2018)

The link between injector tip cleanliness and engine-out PN



Without detergent:

- Increase in particulate emissions over 4 hours

With detergent:

- No increase in particulate emission over 4 hours test cycle
- Detergents can actively decrease particulate emissions over 8 hour 'clean-up' cycle

Fuel	Detergent Content	Aromatics (vol.%)	T90 (°C)
A	0	40	134.3
B	Medium	40	134.3
C	High	40	134.3
D	0	20	173.9

SAE 2017-01-0808

Conclusions

❑ ICE Target

- 45+% BTE
- **High octane (RON 96+) / Low PMI fuel**

❑ Challenge1: LSPI/SPI

- Occurs across all speeds and high load
- Both lubricant and fuel sensitive

❑ Challenge 2: PM/PN

- **Injector coking biggest source**
- **Low PM/PN fuels (PM Index < 1.80) depress LSPI**
- **PM Index found to be a superior predictor of PM/PN than both the PN Index and the Moriya Index**
- There is a PM spike associated with every SPI event
- C9+ heavy aromatics increase PM/PN chemically and physically
- Lowering fuel T90 and FBP decreases PM/PN by wall wetting
- Increasing fuel VP decreases PM/PN
- **Significant nucleation mode peak at about 10 nm**
- TWC should be expected to remove volatiles (~10 nm peak); **need experimental data!**

$$PM\ index = \sum_{i=1}^n \left[\frac{DBE_i + 1}{VP_i} \right] W_{ti}$$

