

CRC Report No. AVFL-44

**First Investigation of Ducted Fuel
Injection on a Retrofitted Heavy-Duty
Multi-Cylinder Production Engine**

Final Report

October 2025



COORDINATING RESEARCH COUNCIL, INC.
1 CONCOURSE PARKWAY • SUITE 800 • ATLANTA, GA 30328

The Coordinating Research Council, Inc. (CRC) is a non-profit corporation supported by the petroleum and automotive equipment industries with participation from other industries, companies, and governmental bodies on research programs of mutual interest. CRC operates through the committees made up of technical experts from industry and government who voluntarily participate. The five main areas of research within CRC are: air pollution (atmospheric and engineering studies); aviation fuels, lubricants, and equipment performance; heavy-duty vehicle fuels, lubricants, and equipment performance (e.g., diesel trucks); light-duty vehicle fuels, lubricants, and equipment performance (e.g., passenger cars); and sustainable mobility (e.g., decarbonization). CRC's function is to provide the mechanism for joint research conducted by industries that will help in determining the optimum combination of products. CRC's work is limited to research that is mutually beneficial to the industries involved. The final results of the research conducted by, or under the auspices of, CRC are available to the public.

LEGAL NOTICE

This report was prepared by Sandia National Laboratory as an account of work sponsored by the Coordinating Research Council (CRC). Neither the CRC, members of the CRC, Sandia National Laboratory, nor any person acting on their behalf: (1) makes any warranty, express or implied, with respect to the use of any information, apparatus, method, or process disclosed in this report, or (2) assumes any liabilities with respect to use of, inability to use, or damages resulting from the use or inability to use, any information, apparatus, method, or process disclosed in this report. In formulating and approving reports, the appropriate committee of the Coordinating Research Council, Inc. has not investigated or considered patents which may apply to the subject matter. Prospective users of the report are responsible for protecting themselves against liability for infringement of patents.

First investigation of ducted fuel injection on a retrofitted heavy-duty multi-cylinder production engine

Ryan M. Ogren¹, Kirby J. Baumgard², Vishnu Radhakrishna³, Robert C. Kempin³,
and Charles J. Mueller³

¹John Deere, ²Baumgard Technologies, ³Sandia National Laboratories

ABSTRACT

Ducted fuel injection (DFI) was tested for the first time on a production multi-cylinder engine using a John Deere Model 6090 heavy-duty diesel engine. Design-of-experiments (DoE) testing was carried out for DFI with a baseline ultra-low sulfur diesel (ULSD) fuel as well as three fuels with lower lifecycle carbon-dioxide (CO₂) emissions: renewable diesel, neat biodiesel (from soy), and a 50/50 blend by volume of biodiesel with renewable diesel. For all fuels tested, DFI enabled simultaneous reductions of engine-out emissions of soot and nitrogen oxides (NO_x) with late injection timings. DoE data were used to develop individual calibrations for steady-state testing with each fuel using the ISO 8178 eight-mode off-road test cycle. Over the ISO 8178 test, DFI with a 5-duct configuration and B50R50 fuel reduced soot and NO_x by 87% and 42%, respectively, relative to the production hardware. Soot reductions generally decreased with increasing engine load. Hydrocarbon and carbon monoxide emissions tended to increase with DFI but were not excessive over the ISO 8178 test. Brake-specific energy consumption generally increased with DFI due to the use of retarded injection timings and exhaust-gas recirculation to achieve the desired NO_x reductions but was less than or equal to that for conventional diesel combustion with ULSD at a similar NO_x level. Significant deposits were encountered on one cylinder when running at idle with the ULSD fuel only, but this was mitigated by replacing the corresponding fuel injector (which showed deformation at the exits of two of its orifices) and using a fuel detergent additive in subsequent testing. In all, the engine was successfully operated for over 300 hours in the DFI configuration. Research areas for improved DFI implementation are identified.